

Practical delivery and quick to assemble

Flat-Pack



Practical delivery and quick to assemble
 The development of the flat-pack version of the NT Box is SCHÄFER's response to the growing logistics and assembly demands of network technology.
 The base model consists of the SCHÄFER low-cost, modular, standard wall-mounted system with removable doors and side panels. The flat-pack NT Boxes, however, are designed to have the lowest possible packaging volume, while keeping the required assembly work to a minimum.
 In only four steps, the complete distributor - either on the ground or wall-mounted - can be assembled by one person. Our standard range of accessories enables the Box to be extended as required.

- Cost effective and efficient assembly on site in only four steps and by only one person
- Easy installation and maintenance: removable doors and side panels guarantee optimum accessibility from all sides, standard accessories

- Economically efficient: maximum saving of transport volume
- Economically efficient: maximum saving of storage space, low space requirement despite high versatility



1 Preparation for assembly: check that all individual parts have been delivered. The rear panel can be used as a drilling template. Mark the drill hole positions, drill the holes and attach the rear panel to the wall. Alternatively, the Box can be assembled on the ground



2 Slide the floor into the longitudinal slits provided and secure it with corner connectors, which are then fastened into place by screws



3 Erect the vertical mounting angles and screw them into place



4 Place the roof on the top of the vertical mounting angles and bolt into place. Insert corner connectors and screw them tight



5 Mount the 482.6 mm (19") angles in the required position and slide the left and right hand side panels into place. Then, install the glass door by first inserting the hinge pin into the top drill hole, before allowing the bottom pin to slide into the lower hole. Secure the door at the top with the red securing ring



Order no.	7406500	7409500	7412500	7415500	7418500	7421500
Useable height U (mm)	6 (350)	9 (475)	12 (600)	15 (750)	18 (875)	21 (1000)
External dimensions in mm (W x D)	570 x 500					
EXPRESS RANGE						
Delivery comprises						
Rear wall panel	1	1	1	1	1	1
Top and bottom modules with brush strips	2	2	2	2	2	2
Corner connectors for mounting the frame and vertical angles	4	4	4	4	4	4
Side panels, passive ventilated	2	2	2	2	2	2
Glass door, front, with lock	1	1	1	1	1	1
482.6 mm (19") mounting angles for front installation	2	2	2	2	2	2
Earthing kit	1	1	1	1	1	1

NT Box system accessories (from page 87) and general system accessories (from page 90)

Light grey RAL 7035